

SYNKOLOID COMPANY -- SYNKO SPACKLING PASTE INTERIOR, SA-100 -- 8030-00N019315

===== Product Identification =====

Product ID:SYNKO SPACKLING PASTE INTERIOR, SA-100

MSDS Date:05/03/1988

FSC:8030

NIIN:00N019315

MSDS Number: BLWQM

=== Responsible Party ===

Company Name:SYNKOLOID COMPANY

Address:148 E 5TH STREET

City:BAYONNE

State:NJ

ZIP:07002

Country:US

Info Phone Num:201-437-0770

Emergency Phone Num:201-437-0770

CAGE:HO980

=== Contractor Identification ===

Company Name:SYNKOLOID COMPANY

Address:148 E 5TH STREET

Box:City:BAYONNE

State:NJ

ZIP:07002-4297

Country:US

Phone:201-437-0770

CAGE:HO980

===== Composition/Information on Ingredients =====

Ingred Name:LIGROINE; (MINERAL SPIRITS)

CAS:8032-32-4

RTECS #:OI6180000

Fraction by Wt: 6.2%

OSHA PEL:300 PPM;400 PPM STEL

ACGIH TLV:300 PPM

Ingred Name:XYLENE

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 2.0%

OSHA PEL:100 PPM;150 PPM STEL

ACGIH TLV:100 PPM;150 PPM STEL

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: .9%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingrid Name:METHYL ALCOHOL (METHANOL)
 CAS:67-56-1
 RTECS #:PC1400000
 Fraction by Wt: .1%
 OSHA PEL:S,200PPM/250STEL
 ACGIH TLV:S,200PPM/250STEL; 93
 EPA Rpt Qty:5000 LBS
 DOT Rpt Qty:5000 LBS

Ingrid Name:ACETIC ACID, MERCURY (2+) SALT; (MERCURIC ACETATE)
 CAS:1600-27-7
 RTECS #:AI8575000
 Fraction by Wt: .02%

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
 Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
 Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
 Health Hazards Acute and Chronic:INHALATION OF HIGH CONCENTRATIONS OF
 MINERAL SPIRITS MAY HAVE RESULTS RANGING FROM MILD DEPRESSION TO
 CONVULSIONS & LOSS OF CONSCIOUSNESS.
 Explanation of Carcinogenicity:NOT RELEVANT.
 Effects of Overexposure:SEE HEALTH HAZARDS.
 Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYE:FLUSH WITH COOL WATER FOR AT LEAST 15 MINUTES. IF
 IRRITATION PERSISTS, GET MD. INGEST:DO NOT INDUCE VOMITING, CALL
 MD. INHAL:REMOVE FROM EXPOSURE AND CALL MD. SKIN:WASH WITH SOAP &
 WATER.

===== Fire Fighting Measures =====

Flash Point:>200F,>93C
 Extinguishing Media:MEDIA SUITABLE FOR SURROUNDING FIRE .
 Fire Fighting Procedures:COOL CONTAINERS TO AVOID PRESSURE BUILD-UPS.
 WEAR NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT .
 Unusual Fire/Explosion Hazard:CONTAINERS MAY BURST DUE TO ELEVATED
 VAPOR PRESSURE.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. ABSORB WITH
 ABSORBENT, SWEEP OR SCOOP UP, VENTILATED EXPOSED ENCLOSED AREAS.
 Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP FROM HEAT & OPEN FLAME. USE WITH
 ADEQUATE VENTILATION TO KEEP AIR CONTAMINANT LEVEL BELOW EXPOSURE
 LIMITS.
 Other Precautions:AVOID PROLONGED OR REPEATED BREATHING OF VAPORS OR
 SKIN CONTACT. USE AIR SUPPLIED RESCUE EQUIPMENT IN ENCLOSED AREAS.
 COOL EXPOSED CONTAINER WITH WATER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: AVOID BREATHING VAPORS. USE WITH ADEQUATE VENTILATION. NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN.

Ventilation: OPEN WINDOW, OR FAN TO REMOVE SOLVENT VAPORS FROM LOW AREAS.

Protective Gloves: HYDROCARBON INSOLUBLE GLOVES.

Eye Protection: CHEMICAL WORKERS GOGGLES.

Other Protective Equipment: USE FULL LENGTH CLOTHING TO AVOID PROLONGED AND REPEATED SKIN CONTACT.

Work Hygienic Practices: NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health
NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

HCC: N1

Boiling Pt: B.P. Text: 212F, 100C

Vapor Density: HVR/AIR

Evaporation Rate & Reference: SLOWER THAN ETHER

Appearance and Odor: MILD ODOR, HEAVY PASTE

Percent Volatiles by Volume: 33.5

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES
NONE SPECIFIED BY MANUFACTURER.

Stability Condition to Avoid: HIGH TEMPERATURE OR FLAME.

Hazardous Decomposition Products: OXIDES OF CARBON.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.