# SAFETY DATA SHEET

6550

## Section 1. Identification

Product name

: MASON'S SELECT® Concrete Etcher

Product code

: 6550

Other means of

: Not available.

identification

Product type

: Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Paint or paint related material.

Manufacturer

: DUCKBACK PRODUCTS 101 W. Prospect Ave. Cleveland, OHIO 44115

Emergency telephone

number of the company

: (216) 566-2917

**Product Information Telephone Number** 

: (800) 825-5382

Regulatory Information

**Telephone Number** 

: (216) 566-2902

**Transportation Emergency** 

: (800) 255-3924

Telephone Number

## Section 2. Hazards identification

OSHA/HCS status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A

Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 20.1%

(dermal), 20.1% (inhalation)

**GHS label elements** 

Hazard pictograms



Signal word

Warning

Hazard statements

Causes skin irritation.

Causes serious eye irritation.

Precautionary statements

General

: Read label before use. Keep out of reach of children. If medical advice is needed,

have product container or label at hand.

Prevention

: Wear protective gloves. Wear eye or face protection. Wash thoroughly after handling.

Response

: Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

Date of issue/Date of revision

: 4/17/2021

Date of previous issue

: 10/12/2020

Version :7

1/11

MASON'S SELECT® Concrete Etcher

## Section 2. Hazards identification

Storage : Not applicable. Disposal : Not applicable.

Supplemental label

elements

WARNING: This product contains a chemical known to the State of California to cause

Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.

Hazards not otherwise

classified

: None known.

# Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

Other means of identification

: Not available.

### CAS number/other identifiers

Ingredient name	% by weight	CAS number
Hydroxybutanedioic Acid	≥10 - ≤20	6915-15-7
Citric Acid	≥10 - ≤20	77-92-9

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

## Description of necessary first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

## Most important symptoms/effects, acute and delayed

#### Potential acute health effects

Eve contact : Causes serious eye irritation.

Date of issue/Date of revision

: 4/17/2021 Date of previous issue : 10/12/2020

2/11

6550 MASON'S SELECT® Concrete Etcher

SHW-85-NA-GHS-US

Version :7

## Section 4. First aid measures

: No known significant effects or critical hazards. Inhalation

: Causes skin irritation. Skin contact

: No known significant effects or critical hazards. Ingestion

Over-exposure signs/symptoms

: Adverse symptoms may include the following: Eye contact

pain or irritation

watering redness

: No specific data. Inhalation

: Adverse symptoms may include the following: Skin contact

> irritation redness

: No specific data. Ingestion

Indication of immediate medical attention and special treatment needed, if necessary

: Treat symptomatically. Contact poison treatment specialist immediately if large Notes to physician

quantities have been ingested or inhaled.

: No specific treatment. Specific treatments

: No action shall be taken involving any personal risk or without suitable training. It may Protection of first-aiders

be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

Unsuitable extinguishing

media

: None known.

Specific hazards arising

Hazardous thermal

from the chemical

decomposition products

: In a fire or if heated, a pressure increase will occur and the container may burst.

: Decomposition products may include the following materials:

: Use an extinguishing agent suitable for the surrounding fire.

carbon dioxide carbon monoxide

Special protective actions

for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable

training.

Special protective equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is

inadequate. Put on appropriate personal protective equipment.

: 10/12/2020 Version :7 3/11 : 4/17/2021 Date of previous issue Date of issue/Date of revision

6550 MASON'S SELECT® Concrete Etcher

# Section 6. Accidental release measures

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

Small spill

Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

#### Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating. drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

including any incompatibilities

Conditions for safe storage, : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

# Section 8. Exposure controls/personal protection

#### Control parameters

### Occupational exposure limits (OSHA United States)

Ingredient name	CAS#	Exposure limits	
Hydroxybutanedioic Acid	6915-15-7	None.	
Citric Acid	77-92-9	None.	

### Occupational exposure limits (Canada)

Date of issue/Date of revision

: 4/17/2021

Date of previous issue

: 10/12/2020

Version :7

4/11

MASON'S SELECT® Concrete Etcher

# Section 8. Exposure controls/personal protection

Ingredient name	CAS#	Exposure limits	
None.			

### Occupational exposure limits (Mexico)

	CAS#	Exposure limits		
None.				

Appropriate engineering

controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Environmental exposure

controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

#### Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

# Section 9. Physical and chemical properties

#### **Appearance**

: Liquid. Physical state

: Not available. Color : Not available. Odor : Not available. Odor threshold

: 9

Melting point/freezing point : Not available. : 100°C (212°F) Boiling point/boiling range

Version :7 5/11 : 10/12/2020 Date of previous issue : 4/17/2021 Date of issue/Date of revision SHW-85-NA-GHS-US

MASON'S SELECT® Concrete Etcher 6550

# Section 9. Physical and chemical properties

Flash point : Closed cup: Not applicable.

Evaporation rate : 0.09 (butyl acetate = 1)

Flammability (solid, gas) : Not available. Lower and upper explosive

(flammable) limits

: Not available.

Vapor pressure : 2.3 kPa (17.5 mm Hg) [at 20°C]

Vapor density 1 [Air = 1]Relative density : 1.08

Solubility : Not available. Partition coefficient: n-: Not available.

octanol/water

: Not available.

Auto-ignition temperature Decomposition temperature : Not available.

Viscosity Kinematic (40°C (104°F)): >0.205 cm²/s (>20.5 cSt)

Molecular weight Not applicable.

Aerosol product

Heat of combustion : 8.815 kJ/g

# Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

Incompatible materials : No specific data.

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Section 11. Toxicological information

### Information on toxicological effects

### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Hydroxybutanedioic Acid	LD50 Oral	Rat	1600 mg/kg	
Citric Acid	LD50 Oral	Rat	3 g/kg	

Irritation/Corrosion

Date of issue/Date of revision

: 4/17/2021

Date of previous issue

: 10/12/2020

Version :7

6/11

# Section 11. Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
Hydroxybutanedioic Acid	Eyes - Severe irritant	Rabbit		24 hours 750	-
	Skin - Moderate irritant	Rabbit		ug 24 hours 20	
Citric Acid	Eyes - Severe irritant	Rabbit		mg 24 hours 750	
	Skin - Mild irritant	Rabbit		ug 24 hours 500	
	Skin - Moderate irritant	Rabbit		mg 0.5 MI	

#### Sensitization

Not available.

#### Mutagenicity

Not available.

#### Carcinogenicity

Not available.

### Reproductive toxicity

Not available.

#### **Teratogenicity**

Not available.

### Specific target organ toxicity (single exposure)

Not available.

### Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Not available.

Information on the likely

routes of exposure

: Not available.

### Potential acute health effects

Eve contact : Causes serious eye irritation.

Inhalation : No known significant effects or critical hazards.

Skin contact : Causes skin irritation.

Ingestion : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation : No specific data.

Skin contact : Adverse symptoms may include the following:

irritation redness

Ingestion : No specific data.

Date of issue/Date of revision

: 4/17/2021

Date of previous issue

: 10/12/2020

Version :7

7/11

MASON'S SELECT® Concrete Etcher

# Section 11. Toxicological information

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

: Not available.

effects

Potential delayed effects

: Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects

: Not available.

Potential chronic health effects

Not available.

General Carcinogenicity : No known significant effects or critical hazards. : No known significant effects or critical hazards.

Mutagenicity Teratogenicity : No known significant effects or critical hazards. No known significant effects or critical hazards.

Developmental effects

No known significant effects or critical hazards.

Fertility effects

: No known significant effects or critical hazards.

### Numerical measures of toxicity

### Acute toxicity estimates

Route	ATE value
Oral	10397.5 mg/kg

# Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure	
Citric Acid	Acute LC50 160000 µg/l Marine water	Crustaceans - Carcinus maenas - Adult	48 hours	

#### Persistence and degradability

Not available.

#### Bioaccumulative potential

Not available.

#### Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Date of issue/Date of revision

: 4/17/2021

Date of previous issue

Version :7

8/11

MASON'S SELECT® Concrete Etcher

# Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	IATA	IMDG
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name			- 3		
Transport hazard class(es)					
Packing group					
Environmental hazards	No.	No.	No.	No.	No.
Additional information			-		

Special precautions for user :

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according: Not available. to IMO instruments

Proper shipping name

: Not available.

Date of issue/Date of revision

: 4/17/2021

Date of previous issue

: 10/12/2020

Version :7

9/11

MASON'S SELECT® Concrete Etcher

## Section 15. Regulatory information

#### **SARA 313**

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet.

#### California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

#### International regulations

International lists

: Australia inventory (AIIC): Not determined. China inventory (IECSC): Not determined. Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined. Korea inventory (KECI): Not determined.

New Zealand Inventory of Chemicals (NZIoC): Not determined.


Philippines inventory (PICCS): Not determined.

Taiwan Chemical Substances Inventory (TCSI): Not determined.

Thailand inventory: Not determined. Turkey inventory: Not determined. Vietnam inventory: Not determined.

## Section 16. Other information

### Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

#### Procedure used to derive the classification

Classification	Justification
SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A	Calculation method Calculation method

#### History

Date of printing 4/17/2021 Date of issue/Date of revision

: 4/17/2021

Date of previous issue

10/12/2020

Version

: 7

Key to abbreviations

: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

Date of issue/Date of revision

: 4/17/2021

Date of previous issue

: 10/12/2020

Version :7

10/11

MASON'S SELECT® Concrete Etcher

# Section 16. Other information

N/A = Not available SGG = Segregation Group UN = United Nations

Indicates information that has changed from previously issued version.

#### Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

Date of issue/Date of revision

: 4/17/2021

Date of previous issue

: 10/12/2020

Version :7

11/11

